

-40°C Deep Freezer

Large capacity, excellent deep temperature performance, 8 ergonomic designs

Integrative Design of Evaporator and Shelves Faster Temperature Dropping

This product is designed to store vaccines, blood plasma, biological materials etc. Applications could be found in the electronic and chemical laboratories epidemic prevention, hospitals, animal husbandry areas, blood banks and research institutes

● Performance

- Temperature adjustable range:-20°C--40°C
- Microprocessor control, digital display of temperature
- Imported high efficiency Compressor, CFC-free Refrigerant
- Germany EBM brand Fan, high density insulation foam
- Evaporator and Condenser system, guarantee freezing efficiency and uniformity of temperature
- Ergonomic design, more reliable and easy to operate
- High density insulation foam

● Safety System

- Multiple alarm functions: Higher or lower temperature alarm, sensor malfunction alarm, power off alarm
- Two kinds of alarm indicators : Audible buzzing alarm, visual flashing alarm
- Start up delay protection

● Ergonomic Design



- Double doors design with lock respectively
- Ingenious design of lock, double padlock can be used, providing more safety and reliable
- Door handle, easier to open and close
- Drawer, more convenient to use
- Broad voltage tolerance design, applicable for voltage range 198v-238v
- LED digital display for easy observation
- Equipped with lockable casters, easy to move

-40°C Deep Freezer



Specification

Item Code	DW-40L508
Capacity(L)	490
Voltage/Frequency	220/50 220/60
Power(W)	430
Temp.range(°C)	-20--40
Big/Small Drawer	4/6
Cabinet	Upright
Interior Dimensions(mm)(W*D*H)	685*650*1228
Exterior Dimensions(mm)(W*D*H)	895*840*1860
Packing Dimensions(mm)(W*D*H)	965*945*2040
Net/gross Weight(kg)	164/170
Container Load(sets) 20'/40'/40'H	12/24/24
Certificate	CE



-40°C Deep Freezer

-40°C Deep Freezer



Item Code	DW-40L92	DW-40L188	DW-40L262	DW-40L428	DW-40L626	DW-40W100	DW-40W255	DW-40W380
Capacity(L)	92	188	262	428	626	100	255	380
Voltage/Frequency	220/50	220/50	220/50 220/60	220/50	220/50	220/50	220/50	220/50 220/60
Power(W)	220	290	340	1200	700	260	410	550
Temp.range(°C)	-10~-40	-10~-40	-10~-40	-10~-40	-20~-45	-20~-40	-20~-40	-20~-40
Drawer/Shelve	3/-	7/-	7/-	5/-	/3	/	/	/
Cabinet	Upright	Upright	Upright	Upright	Upright	Chest	Chest	Chest
Interior Dimensions(mm)(W*D*H)	465*440*645	380*420*1225	480*465*1430	760*630*1300	760*630*1310	500*385*625	1040*430*605	1376*457*625
Exterior Dimensions(mm)(W*D*H)	597*610*860	597*610*1475	657*685*1665	910*835*1990	1035*900*1980	680*600*805	1243*633*838	1550*633*838
Packing Dimensions(mm)(W*D*H)	659*699*934	659*699*1548	732*745*1756	1065*975*2125	1072*954*2130	735*645*855	1310*750*880	1630*755*880
Net/gross Weight(kg)	46/51	63/71	88/93	298/314	298/314	43/46	69/81	82/89
Container Load(sets) 20'/40'/40'H	54/108/108	27/54/54	24/48/48	24/48/48	12/24/24	54/108/162	24/54/81	18/42/63
Certificate	/	/	CE	CE	/	/	CE	CE